

HOW TO ORDER

STEP 1 » Choose Recessed Poke-Through (MOI8-REC)



STEP 2 » Choose Configuration * (20amp standard, 15amp available) Select 4 sections to complete the configuration

*Configuration does not include communication components

	2-inch NPS » 2-inch NPS opening
	3/4-inch NPS » 3/4-inch NPS opening
	AV » 6-port AV
	AV-C2 » 6-port AV & (2) communication openings
	Blank »
	C8 » (8) communication openings

	DB15 » (2) DB-15 openings
	DP » Decora receptacle
	DPUSB » 2USB (AC) receptacle
	P4-C8 » MAAP module opening
	P4 » (4) single power
	P5 » (5) single power

EXAMPLE: MOI8-REC-DP-DP-P5-C8

STEP 3 » Choose Cover Finish (AHC-CED Cover only for MOI8-REC)

Stainless Steel
Add: **-SS**

Brass
Add: **-BR**

Black
Add: **-BK**

EXAMPLE: » MOI8-REC-DP-DP-P5-C8-SS-AHC-CED

STEP 4 » Specify Slab Thickness

» Must specify when ordering to achieve proper collar size of threaded pipe.

» Minimum slab thickness for MOI8 is 6 inches.

** Standard and MINIMUM length is 8 inches.
Larger custom lengths available.

EXAMPLE

MOI8-REC-DP-DP-P5-C8-SS-AHC-CED-8

