

RCFB-2

Part numbers/UPC Codes

RCFB-2	784149400159
RCFB-2-A	784149011204
RCFB-2-DB	784149011211

Description

The Lew Electric RCFB-2 series is a two gang, recessed, divided drop in style floor box with a solid metal hybrid cover (two 1 ¼" screw plugs inside of each single flip lid). The floor box allows you to plug into the recessed receptacle and not have the plugs visible or at the surface, creating a low profile look and removing the tripping hazard from the plug sticking above the floor. Rubber grommets are included to protect the cords around the threaded screw hole openings in the brass cover when they are in use. Inside the floor box are two UL listed, 15 AMP (TR) duplex receptacles. A Lew RRP-2-PQ quad port Comm./Data device is also included to replace one of the receptacles if warranted. This allows for line voltage and Comm./Data to be utilized in the same box. The RCFB-2 is a watertight assembly with its watertight screw plugs and durable ¼" neoprene gaskets that go under the flip lids. A second neoprene gasket goes between the cover and the finished floor, preventing water from accessing the box below. The UL listed, stamped steel box is designed for subfloor installation and the ½" ko's on all sides of the box makes cable entry easy and convenient.

Color Options

- Aluminum
- Brass
- Dark Bronze

Compliance and Certifications

- Box UL #E345966
- Outlet UL #E309821
- Meets NEMA WD1-1983 requirement

Downloads

- [Installation Instructions](#)
- [PDF Drawing](#)
- [DWG Drawing](#)

Warranty

1 YEAR

Country Of Origin

CHINA



Also includes RRP-2-PQ



Brass (RCFB-2)



Aluminum (RCFB-2-A)



Dark Bronze (RCFB-2-DB)

RCFB-2

Material Specifications

BOX/HOUSING

Stamped Steel

COVER/FLANGE

Painted or Solid Metal

GROUNDING SCREW OR OTHER

- Adjustment Sleeve: Stamped Steel
- Device mount plate: Stamped Steel
- Divider: Stamped Steel
- Mounting Screws: (4) $\frac{9}{32} \times 1\frac{1}{4}$ ", (4) $\frac{9}{32} \times \frac{3}{4}$ ", (2) $\frac{9}{32} \times \frac{1}{2}$ "

GASKET

Neoprene

Mechanical Specifications

CONDUIT SELECTIONS

- (20) $\frac{1}{2}$ " sides
- (8) $\frac{1}{2}$ " bottom

DIMENSIONS

- Cover Dimensions: 8.5" x 5"
- Overall Height: 3.96"

Electrical Specifications

RECEPTACLE(S) TYPE

Duplex 15A

Product Features

APPLICATION SELECTOR

Residential

PRODUCT TYPE

Floor Box

SERVICE CAPACITY

Dual

PLUG CONNECTION TYPE

Recessed

OTHER

- Includes rubber grommets to keep cords safe
- watertight close up plugs and gasket under flip lid keeps water out
- For subfloor application

FINISH FLOOR TYPE

- Carpet
- Tile
- Wood

BOX CAPACITY

2 GANG

