

# Under Cabinet Power

## KITCHEN POWER SOLUTIONS

### UCPDR20

#### Part numbers/UPC Codes

UCPDR20ACD-SS	784149410516
UCPDR20GACD-SS	784149410523
UCPDR20GD-SS	784149410530

#### Description

The Lew Electric UCPDR series is an innovative under cabinet pop down power assembly that discreetly hides inside your upper kitchen cabinet. When not in use, the receptacle remains completely concealed behind a sleek, round stainless steel top that blends seamlessly with your cabinet trim. With a simple press, the unit pops down to reveal a powerful 20 Amp electrical outlet. Available in three unique styles, this series is simple to install and requires only a 3¾-inch round cutout in the bottom of your upper cabinet. Once inserted, the unit is secured using the included threaded flange, and its compact design takes up about the same amount of space as a drinking glass. To power the unit, the included 2-foot cord is hardwired into a standard junction box (not included), making it ideal for both new kitchen builds and remodels. Other features include 340 degrees of rotation and tamper resistant plugs.

#### Compliance and Certifications

- ETL listed for USA installations, #4004534
- cETL listed for Canada installation, #4004534
- CSA approved for Canada, #C22.2
- Conforms to UL standard 498 and 943 (GFI options)
- UL listed receptacle, #E491706 (DECORA/USB)
- UL listed receptacle, #E473428 (GFCI)



#### Downloads

[Installation Instructions](#)  
[ETL Certification Sheet](#)

[PDF Drawing: UCPDR20ACD-SS](#)  
[DWG Drawing: UCPDR20ACD-SS](#)

[PDF Drawing: UCPDR20GACD-SS](#)  
[DWG Drawing: UCPDR20GACD-SS](#)

[PDF Drawing: UCPDR20GD-SS](#)  
[DWG Drawing: UCPDR20GD-SS](#)

#### Warranty

2 YEARS

#### Country Of Origin

CHINA



Stainless (UCPDR20ACD-SS)



Stainless (UCPDR20GACD-SS)



Stainless (UCPDR20GD-SS)



Closed under cabinet

# Under Cabinet Power

## KITCHEN POWER SOLUTIONS

### UCPDR20

#### Material Specifications

**BOX/HOUSING**

Plastic

**COVER/FLANGE**

Painted or Solid Metal

**GROUNDING SCREW OR OTHER**

- Locknut: Plastic
- Locking device: Plastic
- 2' wiring whip

**GASKET**

Neoprene

#### Mechanical Specifications

**DIMENSIONS**

- Flange Diameter: 4"
- Cover Diameter: 3.25"
- Locking flange diameter: 4.875"
- In use depth: 4.3"-6.3"
- Closed height inside cabinet: 10"-12"

#### Electrical Specifications

**RECEPTACLE(S) TYPE**

Duplex 20A Decora  
or  
Duplex 20A GFCI

**OTHER**

- Model UCPDR20GD:  
USB-A charging port ( 27W Class 2 QC3.0)  
USB-C charging port (30W Class 2 PD 2.0+QC3.0)
- Model UCPDR20GACD:  
USB-A (30W Quick Charge 3.0)  
USB-C (30W:PD 2.0)

#### Product Features

**APPLICATION SELECTOR**

Kitchen

**PRODUCT TYPE**

Under Cabinet Power Box

**SERVICE CAPACITY**

Single

**PLUG CONNECTION TYPE**

Below Cabinet

**OTHER**

- 340 degree rotation
- Includes 2 foot power whip

