

Under Cabinet Power

KITCHEN POWER SOLUTIONS

UCPDR20

Part numbers/UPC Codes

UCPDR20ACD-SS	784149410516
UCPDR20GACD-SS	784149410523
UCPDR20GD-SS	784149410530

Description

The Lew Electric UCPDR series is an innovative under cabinet pop down power assembly that discreetly hides inside your upper kitchen cabinet. When not in use, the receptacle remains completely concealed behind a sleek, round stainless steel top that blends seamlessly with your cabinet trim. With a simple press, the unit pops down to reveal a powerful 20 Amp electrical outlet. Available in three unique styles, this series is simple to install and requires only a 3 3/4-inch round cutout in the bottom of your upper cabinet. Once inserted, the unit is secured using the included threaded flange, and its compact design takes up about the same amount of space as a drinking glass. To power the unit, the included 2-foot cord is hardwired into a standard junction box (not included), making it ideal for both new kitchen builds and remodels. Other features include 340 degrees of rotation and tamper resistant plugs.

Compliance and Certifications

- ETL listed for USA installations, #4004534
- cETL listed for Canada installation, #4004534
- CSA approved for Canada, #C22.2
- Conforms to UL standard 498 and 943 (GFI options)
- UL listed receptacle, #E491706 (DECORA/USB)
- UL listed receptacle, #E473428 (GFCI)



Downloads

[Installation Instructions](#)
[ETL Certification Sheet](#)

[PDF Drawing: UCPDR20ACD-SS](#)
[DWG Drawing: UCPDR20ACD-SS](#)

[PDF Drawing: UCPDR20GACD-SS](#)
[DWG Drawing: UCPDR20GACD-SS](#)

[PDF Drawing: UCPDR20GD-SS](#)
[DWG Drawing: UCPDR20GD-SS](#)

Warranty

2 YEARS

Country Of Origin

CHINA



Stainless (UCPDR20ACD-SS)



Stainless (UCPDR20GACD-SS)



Stainless (UCPDR20GD-SS)



Closed under cabinet

Under Cabinet Power

KITCHEN POWER SOLUTIONS

UCPDR20

Material Specifications

BOX/HOUSING

Plastic

COVER/FLANGE

Painted or Solid Metal

GROUNDING SCREW OR OTHER

- Locknut: Plastic
- Locking device: Plastic
- 2' wiring whip

GASKET

Neoprene

Mechanical Specifications

DIMENSIONS

- Flange Diameter: 4"
- Cover Diameter: 3.25"
- Locking flange diameter: 4.875"
- In use depth: 4.3"-6.3"
- Closed height inside cabinet: 10"-12"

Electrical Specifications

RECEPTACLE(S) TYPE

Duplex 20A Decora
or
Duplex 20A GFCI

OTHER

- Model UCPDR20GD:
USB-A charging port (27W Class 2 QC3.0)
USB-C charging port (30W Class 2 PD 2.0+QC3.0)
- Model UCPDR20GACD:
USB-A (30W Quick Charge 3.0)
USB-C (30W:PD 2.0)

Product Features

APPLICATION SELECTOR

Kitchen

PRODUCT TYPE

Under Cabinet Power Box

SERVICE CAPACITY

Single

PLUG CONNECTION TYPE

Below Cabinet

OTHER

- 340 degree rotation
- Includes 2 foot power whip

