

PUR20AC2PD

Part numbers/UPC Codes

PUR20AC2PD-BK	784149410134
PUR20AC2PD-SS	784149410141
PUR20AC2PD-WT	784149410158

Description

The PUR20AC2PD series is a round Kitchen Countertop Pop-Up Assembly that features two 20 Amp Decora/2USB (AC) duplex receptacle.

Engineered for full compliance with the 2023 National Electrical Code (NEC 406.5E), the PUR20AC2PD series is fully approved for use in kitchen countertops and other wet locations across the United States and Canada. It includes a UL-listed tamper-resistant receptacle, ETL listing for the U.S., and cETL/CSA approvals for Canada. With an IP43 rating and successful completion of the UL 498 spill test, this pop-up outlet is built to withstand spills and kitchen messes. A built-in gasket below the trim prevents moisture from leaking into the cutout or cabinetry, making it a reliable power source in high-use, moisture-prone areas like islands, bars, and pantries. Installation requires only a single 3 ¾ inch round cut in the countertop. This unit includes a 5 foot power cord whip and features 340 degree of rotation for ease of use anywhere on the countertop.

An optional color chip sample book is available.

<https://lewelectric.com/catalog/ct-cc/>

Color Options

- Black
- Stainless
- White

Compliance and Certifications

- ETL listed for USA installations, #4004534
- cETL listed for Canada installation, #4004534
- CSA approved for Canada, #C22.2
- Conforms to UL standard 498 and 943 (GFI options)
- UL listed receptacle, #E491706



Downloads

- [Installation Instructions](#)
- [Installation Video](#)
- [ETL Certification Sheet](#)
- [PDF Drawing](#)
- [DWG Drawing](#)

Warranty

2 YEARS

Country Of Origin

CHINA



Black Metal Cover
(PUR20AC2PD-BK)



Stainless Metal Cover
(PUR20AC2PD-SS)



White Metal Cover
(PUR20AC2PD-WT)

PUR20AC2PD

Material Specifications

BOX/HOUSING

Plastic

COVER/FLANGE

Painted or Solid Metal

GROUNDING SCREW OR OTHER

- Locknut: Plastic
- Locking device: Plastic
- 5' wiring whip

GASKET

Neoprene

Mechanical Specifications

DIMENSIONS

- Flange Diameter: 4"
- Cover Diameter: 3.25"
- Locking flange diameter: 4.875"
- In use height: 10.7"
- Closed depth under counter: 16"

Electrical Specifications

RECEPTACLE(S) TYPE

Duplex 20A Decora 2USB (AC)

OTHER

- USB-A charging port (27W Class 2 QC3.0)
- USB-C charging port (30W Class 2 PD 2.0+QC3.0)

Product Features

APPLICATION SELECTOR

Kitchen

PRODUCT TYPE

Kitchen Countertop Box

PLUG CONNECTION TYPE

Above Surface

OTHER

Must be connected to GFCI circuit

