

## PUR20ACFCMRD

### Part numbers/UPC Codes

PUR20ACFCMRD-BK 784149700730

PUR20ACFCMRD-SS 784149700754

### Description

The PUR20ACFCMRD series is a round Kitchen Countertop Pop-Up Assembly that features a 20 Amp Decora/2USB duplex receptacle and a top cup that holds and uses the core countertop cutout as its cover. It comes in two trim finishes; Black and Stainless. Engineered for full compliance with the 2023 National Electrical Code (NEC 406.5E), the PUR20ACFCMRD series is fully approved for use in kitchen countertops and other wet locations across the United States and Canada. It includes a UL-listed tamper-resistant receptacle, ETL listing for the U.S., and cETL/CSA approvals for Canada. With a successful completion of the UL 498 spill test, this pop-up outlet is built to withstand spills and kitchen messes. A built-in gasket below the trim prevents moisture from leaking into the cutout or cabinetry, making it a reliable power source in high-use, moisture-prone areas like islands, bars, and pantries. Installation requires only a single 3 ¾ inch round cut in the countertop. This unit includes a 5 foot power cord whip and features 340 degree of rotation for ease of use anywhere on the countertop.

### Color Options

- Black
- Stainless

### Compliance and Certifications

- ETL listed for USA installations, #4004534
- cETL listed for Canada installation, #4004534
- CSA approved for Canada, #C22.2
- Conforms to UL standard 498 and 943 (GFI options)
- UL listed receptacle, #E491706



### Downloads

- [Installation Instructions](#)
- [Installation Video](#)
- [ETL Certification Sheet](#)
- [PDF Drawing](#)
- [DWG Drawing](#)

### Warranty

2 YEARS

### Country Of Origin

CHINA



Black (PUR20ACFCMRD-BK)  
shown with sample countertop insert



Stainless (PUR20ACFCMRD-SS)  
shown without countertop insert



## PUR20ACFCMRD

### Material Specifications

#### BOX/HOUSING

Plastic

#### COVER/FLANGE

Painted or Solid Metal

#### GROUNDING SCREW OR OTHER

- Locknut: Plastic
- Locking device: Plastic
- 5' wiring whip

#### GASKET

Neoprene

### Mechanical Specifications

#### DIMENSIONS

- Flange Diameter: 4"
- Cover Diameter: 3.25"
- Locking flange diameter: 4.875"
- In use height: 5.3"
- Closed depth under counter: 12"

### Electrical Specifications

#### RECEPTACLE(S) TYPE

Duplex 20A Decora 2USB (AC)

#### OTHER

- USB-A charging port ( 27W Class 2 QC3.0)
- USB-C charging port (30W Class 2 PD 2.0+QC3.0)

### Product Features

#### APPLICATION SELECTOR

Kitchen

#### PRODUCT TYPE

Kitchen Countertop Box

#### PLUG CONNECTION TYPE

Above Surface

#### OTHER

- Uses countertop cutout as cover
- 340 degree rotation
- Includes 5 foot power whip
- Must be connected to GFCI circuit

