

## PUR20DSD

### Part numbers/UPC Codes

PUR20DSD-BK	784149410226
PUR20DSD-SS	784149410233
PUR20DSD-WT	784149410240

### Description

The PUR20DSD series is a round Kitchen Countertop Pop-Up Assembly that features a 20 Amp Decora receptacle.

Engineered for full compliance with the 2023 National Electrical Code (NEC 406.5E), the PUR20DSD series is fully approved for use in kitchen countertops and other wet locations across the United States and Canada. It includes a UL-listed tamper-resistant receptacle, ETL listing for the U.S., and cETL/CSA approvals for Canada. With an IP43 rating and successful completion of the UL 498 spill test, this pop-up outlet is built to withstand spills and kitchen messes. A built-in gasket below the trim prevents moisture from leaking into the cutout or cabinetry, making it a reliable power source in high-use, moisture-prone areas like islands, bars, and pantries. Installation requires only a single 3 ¾ inch round cut in the countertop. This unit includes a 5 foot power cord whip and features 340 degree of rotation for ease of use anywhere on the countertop.

An optional color chip sample book is available.

<https://lewelectric.com/catalog/ct-cc/>

### Color Options

- Black
- Stainless
- White

### Compliance and Certifications

- ETL listed for USA installations, #4004534
- cETL listed for Canada installation, #4004534
- CSA approved for Canada, #C22.2
- Conforms to UL standard 498 and 943 (GFI options)
- UL listed receptacle, #E229322



### Downloads

- [Installation Instructions](#)
- [Installation Video](#)
- [ETL Certification Sheet](#)
- [PDF Drawing](#)
- [DWG Drawing](#)

### Warranty

2 YEARS

### Country Of Origin

CHINA



Black Metal Cover  
(PUR20DSD-BK)



Stainless Metal Cover  
(PUR20DSD-SS)



White Metal Cover  
(PUR20DSD-WT)



## PUR20DSD

### *Material Specifications*

**BOX/HOUSING**

Plastic

**COVER/FLANGE**

Painted or Solid Metal

**GROUNDING SCREW OR OTHER**

- Locknut: Plastic
- Locking device: Plastic
- 5' wiring whip

**GASKET**

Neoprene

### *Mechanical Specifications*

**DIMENSIONS**

- Flange Diameter: 4"
- Cover Diameter: 3.25"
- Locking flange diameter: 4.875"
- In use height: 5.3
- Closed depth under counter: 8.5"

### *Electrical Specifications*

**RECEPTACLE(S) TYPE**

Duplex 20A Decora

### *Product Features*

**APPLICATION SELECTOR**

Kitchen

**PRODUCT TYPE**

Kitchen Countertop Box

**PLUG CONNECTION TYPE**

Above Surface

**OTHER**

Must be connected to GFCI circuit

