

PUR20GFIACFCMRD

Part numbers/UPC Codes

PUR20GFIACFCMRD-BK 784149700815

PUR20GFIACFCMRD-SS 784149700839

Description

The PUR20GFIACFCMRD series is a round Kitchen Countertop Pop-Up Assembly that features a 20 Amp GFCI/2USB single plug receptacle and a top cup that holds and uses the core countertop cutout as its cover. It comes in two trim finishes; Black and Stainless. Engineered for full compliance with the 2023 National Electrical Code (NEC 406.5E), the PUR20GFIACFCMRD series is fully approved for use in kitchen countertops and other wet locations across the United States and Canada. It includes a UL-listed tamper-resistant receptacle, ETL listing for the U.S., and cETL/CSA approvals for Canada. With successful completion of the UL 498 spill test, this pop-up outlet is built to withstand spills and kitchen messes. A built-in gasket below the trim prevents moisture from leaking into the cutout or cabinetry, making it a reliable power source in high-use, moisture-prone areas like islands, bars, and pantries. This outlet also meets the ANSI/UL 943 standard for ground fault circuit interrupters (GFCI), making it a reliable and code-compliant solution for countertop power needs. Installation requires only a single 3¾ inch round cut in the countertop. This unit includes a 5 foot power cord whip and features 340 degree of rotation for ease of use anywhere on the countertop.

Color Options

- Black
- Stainless

Compliance and Certifications

- ETL listed for USA installations, #4004534
- cETL listed for Canada installation, #4004534
- CSA approved for Canada, #C22.2
- Conforms to UL standard 498 and 943 (GFI options)
- UL listed receptacle, #E473428



Downloads

- [Installation Instructions](#)
- [Installation Video](#)
- [ETL Certification Sheet](#)
- [PDF Drawing](#)
- [DWG Drawing](#)

Warranty

2 YEARS

Country Of Origin

CHINA



Black (PUR20GFIACFCMRD-BK)
shown without countertop insert



Stainless (PUR20GFIACFCMRD-SS)
shown with sample countertop insert



PUR20GFIACFCMRD

Material Specifications

BOX/HOUSING

Plastic

COVER/FLANGE

Painted or Solid Metal

GROUNDING SCREW OR OTHER

- Locknut: Plastic
- Locking device: Plastic
- 5' wiring whip

GASKET

Neoprene

Mechanical Specifications

DIMENSIONS

- Flange Diameter: 4"
- Cover Diameter: 3.25"
- Locking flange diameter: 4.875"
- In use height: 5.3"
- Closed depth under counter: 12"

Electrical Specifications

RECEPTACLE(S) TYPE

- Single GFCI 2USB (AC)
- class 2 5VDC 4 8A max

OTHER

- USB-A (12W)
- USB-C (15W)

Product Features

APPLICATION SELECTOR

Kitchen

PRODUCT TYPE

Kitchen Countertop Box

PLUG CONNECTION TYPE

Above Surface

OTHER

- Uses countertop cutout as cover
- 340 degree rotation
- Includes 5 foot power whip

